

- 1 Unique identification code of the product-type: **PRINT HPL STRATIFICATO thickness $\geq 2,0$ mm**
2. Intended uses: **HPL laminate used as internal wall and ceiling finishes**
3. Manufacturer: **ABET LAMINATI spa - Viale Industria, 21 - 12042 BRA (CN) - Italy**
Tel. +39 0172 419 111 - Fax: +39 0172 431571 - Email: abet@abet-laminati.it
4. Systems of AVCP: **system 3**
5. Harmonised standard: **EN 438-7: 2005**
6. Notify Body: **CSI SpA - n° 0497**
7. Declared performance

Essential characteristics	Performance
Reaction to fire	<p>D-s2,d0 thickness ≥ 2 mm mounted on aluminium tubular rods, without interposition of insulating layer</p> <p>C-s2,d0 thickness ≥ 6 mm mounted on aluminium tubular rods</p> <p>D-s2,d0 thickness ≥ 6 mm fixed on any kind of frame</p> <p>B-s1,d0 thickness ≥ 12 mm fixed on any kind of frame</p>
Resistance to fire	NPD
Water vapour permeability	NPD
Resistance to fixings	<p>250 N (2mm)</p> <p>1000 N (4 mm)</p> <p>2000 N (6 mm)</p> <p>3000 N (8 mm)</p> <p>4000 N (≥ 10 mm)</p>
Direct airborne sound insulation	NPD
Flexural tensile strength	PASS
Thermal resistance/conductivity	NPD
Release of formaldehyde	Class E1
Sound absorption	NPD
Durability Resistance to wet conditions Density	<p>PASS</p> <p>≥ 1350 kg/m³</p>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by
Bra, 24/10/2019



Luciano Menegaldo
Technology Department