

<b>ABET LAMINATI</b>	<b>DECLARATION OF PERFORMANCE</b> <b>No. 001/EDF</b>	Rev. 3
----------------------	---	--------

1. Unique identification code of the product-type: **MEG F1 thickness  $\geq 2,0$  mm**
2. Uses: **HPL laminate used as external wall and ceiling finishes**
3. Manufacturer: **ABET LAMINATI spa - Viale Industria, 21 - 12042 BRA (CN) - Italy**  
**Tel. +39 0172 419 111 - Email: abet@abet-laminati.it**
4. System of AVCP: **system 1 – system 3**
5. Harmonised standard: **EN 438-7: 2005**
6. Notify Body: **CSI SpA - n° 0497**
7. Declared performance

Essential characteristics	Performance		
<b>Reaction to fire</b>	B-s1,d0    thickness $\geq 6$ mm mounted on aluminium tubular rods  D-s2,d0    2 mm $\leq$ thickness $< 6$ mm mounted on aluminium tubular rods		
<b>Resistance to fire</b>	NPD		
<b>Water vapour permeability</b>	NPD		
<b>Resistance to fixings</b>	250 N (2 mm) 1000 N (4 mm)	2000 N (6 m) 3000 N (8 mm)	4000 N ( $\geq 10$ mm)
<b>Direct airborne sound insulation</b>	NPD		
<b>Flexural tensile strength</b>	PASS		
<b>Thermal resistance/conductivity</b>	NPD		
<b>Thermal shock resistance</b>	PASS		
<b>Release of formaldehyde</b>	Class E1		
<b>Durability</b> Resistance to wet conditions Density	PASS $\geq 1350$ kg/m <sup>3</sup>		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Bra, 30/10/2023

  
 Simone Abrate  
 Technical Director