

|                       |                                                         |        |
|-----------------------|---------------------------------------------------------|--------|
| <b>ABET LAMINATI®</b> | <b>DECLARATION OF PERFORMANCE</b><br><b>No. 002/CGF</b> | Rev. 5 |
|-----------------------|---------------------------------------------------------|--------|


1. Unique identification code of the product-type: **PRINT HPL STRATIFICATO F1 thickness  $\geq 2,0$  mm**
2. Intended use: **HPL laminate used as internal wall and ceiling finishes**
3. Manufacturer: **ABET LAMINATI spa - Viale Industria, 21 - 12042 BRA (CN) - Italy**  
**Tel. +39 0172 419 111 - Email: info@abetlaminati.com**
4. System of AVCP: **system 1**
5. Harmonised standard: **EN 438-7: 2005**
6. Notify Body: **CSI SpA - n° 0497**
7. Performance

| Essential characteristics                                                | Performance                                                                                                                                                                                                                                                   |
|--------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Reaction to fire</b>                                                  | B-s1,d0 thickness 2 mm $\leq$ thickness < 6 mm<br>Mechanically fixed on metal frame, without interposition of insulating layer<br><br>B-s1,d0 thickness $\geq 6$ mm<br>Mechanically fixed on wooden or metal frame, without interposition of insulating layer |
| <b>Resistance to fire</b>                                                | NPD                                                                                                                                                                                                                                                           |
| <b>Water vapour permeability</b>                                         | NPD                                                                                                                                                                                                                                                           |
| <b>Resistance to fixings</b>                                             | 250 N (2 mm)      3000 N (8 mm)<br>1000 N (4 mm)      4000 N ( $\geq 10$ mm)<br>2000 N (6 mm)                                                                                                                                                                 |
| <b>Direct airborne sound insulation</b>                                  | NPD                                                                                                                                                                                                                                                           |
| <b>Flexural tensile strength</b>                                         | PASS                                                                                                                                                                                                                                                          |
| <b>Thermal resistance/conductivity</b>                                   | NPD                                                                                                                                                                                                                                                           |
| <b>Release of formaldehyde</b>                                           | Class E1                                                                                                                                                                                                                                                      |
| <b>Sound absorption</b>                                                  | NPD                                                                                                                                                                                                                                                           |
| <b>Durability</b><br>Resistance to immersion in boiling water<br>Density | PASS<br><br>$\geq 1350$ kg/m <sup>3</sup>                                                                                                                                                                                                                     |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Bra, 06/10/2025

  
Simone Abrate  
Technical Director