


ABET LAMINATI®	DECLARATION OF PERFORMANCE No. 004/CGS	Rev. 5
-----------------------	---	--------

- 1 Unique identification code of the product-type: **PRINT HPL STRATIFICATO thickness $\geq 2,0$ mm**
- 2 Intended uses: **HPL laminate used as internal wall and ceiling finishes**
- 3 Manufacturer: **ABET LAMINATI spa - Viale Industria, 21 - 12042 BRA (CN) - Italy**
Tel. +39 0172 419 111 - Email: info@abetlaminati.com
- 4 Systems of AVCP: **system 3**
- 5 Harmonised standard: **EN 438-7: 2005**
- 6 Notify Body: **CSI SpA - n° 0497**
- 7 Declared performance

Essential characteristics	Performance
Reaction to fire	D-s2,d0 thickness ≥ 2 mm Mechanically fixed on metal frame, without interposition of insulating layer C-s2,d0 thickness ≥ 6 mm Mechanically fixed on metal frame D-s2,d0 thickness ≥ 6 mm fixed on any kind of frame B-s1,d0 thickness ≥ 12 mm fixed on any kind of frame
Resistance to fire	NPD
Water vapour permeability	NPD
Resistance to fixings	250 N (2mm) 1000 N (4 mm) 2000 N (6 mm) 3000 N (8 mm) 4000 N (≥ 10 mm)
Direct airborne sound insulation	NPD
Flexural tensile strength	PASS
Thermal resistance/conductivity	NPD
Release of formaldehyde	Class E1
Sound absorption	NPD
Durability Resistance to immersion in boiling water Density	PASS ≥ 1350 kg/m ³

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by
Bra, 06/10/2025


Simone Abrate
Technical Director