


<b>ABET LAMINATI</b>	<b>DECLARATION OF PERFORMANCE</b> <b>No. 004/CGS</b>	Rev. 4
----------------------	---	--------

- 1 Unique identification code of the product-type: **PRINT HPL STRATIFICATO thickness  $\geq 2,0$  mm**
2. Intended uses: **HPL laminate used as internal wall and ceiling finishes**
3. Manufacturer: **ABET LAMINATI spa - Viale Industria, 21 - 12042 BRA (CN) - Italy**  
**Tel. +39 0172 419 111 - Fax: +39 0172 431571 - Email: [abet@abet-laminati.it](mailto:abet@abet-laminati.it)**
4. Systems of AVCP: **system 3**
5. Harmonised standard: **EN 438-7: 2005**
6. Notify Body: **CSI SpA - n° 0497**
7. Declared performance

Essential characteristics	Performance
<b>Reaction to fire</b>	D-s2,d0 thickness $\geq 2$ mm mounted on aluminium tubular rods, without interposition of insulating layer  C-s2,d0 thickness $\geq 6$ mm mounted on aluminium tubular rods  D-s2,d0 thickness $\geq 6$ mm fixed on any kind of frame  B-s1,d0 thickness $\geq 12$ mm fixed on any kind of frame
<b>Resistance to fire</b>	NPD
<b>Water vapour permeability</b>	NPD
<b>Resistance to fixings</b>	250 N (2mm) 1000 N (4 mm) 2000 N (6 mm) 3000 N (8 mm) 4000 N ( $\geq 10$ mm)
<b>Direct airborne sound insulation</b>	NPD
<b>Flexural tensile strength</b>	PASS
<b>Thermal resistance/conductivity</b>	NPD
<b>Release of formaldehyde</b>	Class E1
<b>Sound absorption</b>	NPD
<b>Durability</b> Resistance to immersion in boiling water Density	PASS $\geq 1350$ kg/m <sup>3</sup>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by  
Bra, 01/09/2022

  
Simone Abrate  
Technical Director